

## Annexe and Inner Tent Erection Instructions

### 520 Standard

Before commencing erection of the Annexe it is vital that the awning is fully erected, tensioned and pegged as if the Annexe were not to be used.

**Tip!** Slide approx. 10 grey 'sliding pegging anchors' onto the piping of the PVC splashwall, positioning 3-4 on each side of the Annexe skirt before erecting.

1. Remove the appropriate side panel from your awning. If you'd like to zip the side panel back into the Annexe later, you should leave all the pegs 'in situ' and just withdraw them sufficiently to release the pegging ladders.
2. Attach the Annexe to the awning bringing 1 zip slider from each side to meet in the centre of the zip at head height. Between the points 'O' on diagram 1.
3. Place a rubber pegging ladder on each of the 'sewn-in' pegging anchors at all four corners ensuring that all 3 sides of the Annexe are taut and the Annexe is as square to the awning as possible.
4. Peg the remaining pegging points on each side and across the back.
5. Assemble the frame (as per frame plan in box) and offer the '45 degree goalpost' arrangement into the Annexe body as shown in diagram 1. Be careful not to extend the legs too much at this point to allow easy entry.
6. **Tip!** To stop the frame from slipping, place the spiked foot of each leg into the pegging ladders on the side panel of the awning itself.
7. Tension the roof poles, nesting the corners of the frame into positions E & F and tension the 45 degree angled legs until adequate tension is achieved.
8. Tweak the entire Annexe frame as necessary until the back, sides and roof of the Annexe are drum tight. This is essential to allow rain water to run off and not pool.
9. If an Inner Tent is to be used with the Annexe, first peg down the groundsheet at each corner pegging point, attach the Inner Tent tapes to the frame at the back and then the front ones to the rings in the Annexe roof by the zip. See points 'O'" on diagram 1.
10. For more detailed Inner Tent instructions, please refer to the specific instructions found within the Inner Tent bag.
11. Should you wish to re-fit the original side panel of the awning to offer a little more privacy or to store the bikes and BBQ, simply reverse the awning side panel so the curtains are now facing into the Annexe. Fix into place by bringing 1 zip slider from each side to meet in the centre of the zip at head height, again between the points 'O' on diagram 1.

**NB.** If the side panel is re-fitted or an inner tent used, please ensure that the occupants are fully aware of "Fire Precautions". We strongly recommend that if young children are to sleep in the Annexe, the doorway is left unzipped to provide a quick, unhindered means of escape.

**Diagram 1**

